



beyond standard  
solutions

Sittig Technologies GmbH


Goldgewann 4  
D-65931 Frankfurt / Main  
Germany

Phone:  
+49 / 69 / 37 00 02 - 0

Web:  
www.sittig.de

E-Mail:  
info@sittig.de

# PAXModular NC02-AES67



## Technical details

<b>Function</b>	AES67 Unicast or Multicast Audio streaming via Ethernet 100 Mbit
<b>Voltage</b>	Redundant 24V / DC (18-36V) and/or Poe
<b>Max. power input</b>	500mA
<b>2 Optocoupler inputs</b>	Activated by 0V or +24V signal Maximum capacity: 30V / 50mA / 100mW
<b>2 relay outputs</b>	Two changeover contacts each
<b>2 audio inputs</b>	Electrical symmetric mono
<b>2 audio outputs</b>	Electrical symmetric mono
<b>Communication</b>	Network 100Mbit LAN 10/100Mbit, TCP/IP, AES67 (UDP/RTP)
<b>Dimensions</b>	Case with screw lug and optional top-hat rail bracket height: 66mm width: 130mm length: 140mm
<b>Connection</b>	Screw terminals, RM 3,81
<b>Network connection</b>	RJ45
<b>Monitoring</b>	Voltage and electronic monitoring via watchdog
<b>Signalling</b>	Voltage, audio and error by lamps (LED) on the front panel
<b>Reports</b>	In case of errors, immediate error message to the central control software or a network management system via TCP/IP and/or SNMP